



BRIGHT PEOPLE'S CHOICE



BM152
PowerClamp

- 65ms PEAK-RMS HOLD Captures Maximum RMS Values Of ACA Or ACV As Short As 65ms In Duration
- DATA HOLD Freezes The Displaying Reading For Later View
- PROBE HOLDERS Built-In Probe Storage Holders
- BATTERY COMPARTMENT With Access Door For Easy Battery Replacement
- A-lags INDICATION Unambiguous Indications Of Current Lags Voltage In Inductive Circuits
- HIGH CURRENT Hz Measures Non-Invasive ACA Frequency VIA Clamp Jaws
- HIGH VOLTAGE Hz Measures Noisy High Voltage ACV Frequency VIA Test Leads
- 250µs FAST AUDIBLE CONTINUITY For Quick Open-Short Tests On Switches, Fuses, And Wires
- RESISTANCE Up To 999.9 OHMS, 0.1 OHM Resolution With 600V Protection
- TRANSIENT PROTECTION Up To 6.5kV 1.2/50µs Lightning Surge; More Confidence For Serious Users
- EMC Meets EN61326(1997, 1998/A1), EN61000-4-2(1995), & EN61000-4-3(1996)
- TOTAL POWER FACTOR PF = W / VA Is Used For Nowdays Power-Systems With Harmonics
- FULL POWER PARAMETERS Dual Display Measurements Of "W + PF", "VA + PF", Or "VAR + PF"
- TEMPERATURE Type-K Measurement; Selectable °C Or °F Readings; Comes With BKP60 Bead Probe
- AutoVA FEATURE Sophisticated MCU Controlled Auto-Selection Of ACA, ACV Or DCV Shortens The Time To Measure And Increases The Ease Of Use
- DISPLAY BACKLIGHT For Easy Viewing In The Dark
- 0.5% DCV & ACV BASIC ACCURACY Up To 600 VOLTS, 0.1V Resolution
- TRUE RMS MEASUREMENTS For Non-Sinusoidal Waveforms Of AC Voltages & AC Currents
- PC-COMM INTERFACE CABILITIES Built-In Optical Isolated Data Output Port. Optional Purchase Interface Kit For PC Connection
- LVD CAT III 600V SAFETY Meets EN61010-2-032 CAT III 600V
- RUGGED & DURABLE High-Impact Fire-Retarded Enclosure For Reinforced Safety & Reliability
- AC 1000 AMPS LARGE U-SHAPE CLAMP JAWS Measure ACA Of Large Single Conductor Or Differential ACA Of Multiple Conductors
- STYLISH & HANDY Also Comes With A Soft Pouch For Easy Carrying & Protection