

*SD Card, real time data logger, TDS, Salt, Patent
Pt glass electrode*

CONDUCTIVITY METER

Model : CD-4317SD

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC

The Art of Measurement

SD Card real time data logger

Pt glass electrode

CONDUCTIVITY METER TDS, Salt

Model : CD-4317SD

FEATURES

* One meter for multi purpose operation : Conductivity (Total dissolved solids), Salt measurement.
* Pt glass electrode, high performance for the low conductivity (pure water) measurement.
* Conductivity : 200 uS/2 mS/20 mS/200 mS.
* Salt : 0 to 12 % salt (% weight).
* Conductivity measurement can select Temp. Coefficient of measurement solution.
* ATC for the conductivity measurement.
* Separate probe, easy for operation of different measurement environment.
* Real time SD memory card Datalogger, built-in Clock and Calendar, sampling time can set from 1 sec to 8 hour 59 min. 59 sec.
* Manual datalogger is available, during execute the manual datalogger function, it can set the different location no. (position 1 to position 99).
* Innovation and easy operation, computer is not need to setup extra software, after execute datalogger, just take away the SD card from the meter and plug in the SD card into the computer, it can down load the all the measured value with the time information (year/month/date/ hour/minute/second) to the Excel directly, then user can make the further data or graphic analysis by themselves.
* SD card capacity : 1 GB to 16 GB.
* LCD with green light backlight, easy reading.
* It can default auto power off or manual power off.
* Data hold, record max. and min. reading.
* Microcomputer circuit, high accuracy.
* Power by UM3/AA (1.5 V) x 6 batteries or DC 9V adapter.
* RS232/USB PC COMPUTER interface.
* Wide applications: water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, plating industry, quality control, school & college, water conditioning.

Operating Temperature	Meter	0 to 50 °C.
Operating Humidity	Probe	0 to 60 °C.
Power Supply	Less than 85% R.H.	
Power Current	* Alkaline or heavy duty DC 1.5 V battery (UM3, AA) x 6 PCs, or equivalent.	
	* DC 9V adapter input. (AC/DC power adapter is optional).	
Weight	Normal operation (w/o SD card save data and LCD Backlight is OFF) : <i>Approx. DC 14 mA.</i>	
	When SD card save the data and LCD Backlight is OFF) : <i>Approx. DC 37 mA.</i>	
	* If LCD backlight on, the power consumption will increase approx. 12 mA.	
Dimension	Meter	177 x 68 x 45 mm (7.0 x 2.7 x 1.9 inch)
Accessories Included	Probe	Round, 12 mm Dia. x 157 mm length.
	* Instruction manual.....1 PC * Conductivity/TDS/Salt probe, CDPB-04.....1 PC * Hard carrying case (CA-06).....1 PC	
Optional Accessories	* 1.413 mS Conductivity Standard Solution..... CD-14 SD memory card (2 GB) AC to DC 9V adapter. USB cable, USB-01. RS232 cable, UPCB-02. Data Acquisition software, SW-U801-WIN. Excel data Acquisition software, SE-E802.	

GENERAL SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.	
Display	LCD size : 52 mm x 38 mm LCD with green backlight (ON/OFF).	
Measurement Function	* Conductivity (uS, mS) * TDS (Total Dissolved Solids, PPM) * Salt (% Weight) * Temperature (°C, °F)	
Temperature Compensation	Automatic from 0 to 60 °C (32 - 140 °F), with temperature compensation factor variable between 0 to 5.0% per C.	
Conductivity Probe	Carbon rod electrode for long life.	
Datalogger Sampling Time Setting range	Auto	1 sec to 8 hour 59 min. 59 sec. @ Sampling time can set to 1 second, but memory data may loss.
	Manual	Push the data logger button once will save data one time. @ Set the sampling time to 0 second. @ Manual mode, can also select the 1 to 99 position (Location) no.
Memory Card	SD memory card. 1 GB to 16 GB.	
Advanced setting	* SD memory card Format * Set clock time (Year/Month/Date, Hour/Minute/ Second) * Set sampling time * Auto power OFF management * Set beep Sound ON/OFF * Decimal point of SD card setting * Set temperature unit to °C or °F * Set CD temperature compensation factor	
Data Hold	Freeze the display reading.	
Memory Recall	Maximum & Minimum value.	
Sampling Time of Display	Approx. 1 second.	
Data Output	RS 232/USB PC computer interface. * Connect the optional RS232 cable UPCB-02 will get the RS232 plug. * Connect the optional USB cable USB-01 will get the USB plug.	

ELECTRICAL SPECIFICATIONS (23± 5 °C)

Conductivity (uS, mS)			
Range	Measurement	Resolution	Accuracy
200 uS	0 to 200.0 uS	0.1 uS	± (2% F.S.+1d) * F.S. - full scale
2 mS	0.2 to 2.000 mS	0.001 mS	
20 mS	2 to 20.00 mS	0.01 mS	
200 mS	20 to 200.0 mS	0.1 mS	
* Temperature Compensation : Automatic from 0 to 60 °C (32 - 140 °F), with temperature compensation factor variable between 0 to 5.0% per C. * The accuracy is specified under measurement value ≤ 100 mS. * mS - milli Simens * @ 23± 5°C			

TDS (Total Dissolved Solids)

Range	Measurement	Resolution	Accuracy
200 PPM	0 to 132 PPM	0.1 PPM	± (2% F.S.+1d) * F.S. - full scale
2,000 PPM	132 to 1,320 PPM	1 PPM	
20,000 PPM	1,320 to 13,200 PPM	10 PPM	
200,000 PPM	13,200 to 132,000 PPM	100 PPM	
* Temperature Compensation : Automatic from 0 to 60 °C (32 - 140 °F), with temperature compensation factor variable between 0 to 5.0% per C. * The accuracy is specified under measurement value ≤ 66,000 PPM. * PPM - parts per million * @ 23± 5°C			

Temperature

Function	Measuring Range	Resolution	Accuracy
°C	0 °C to 60 °C	0.1 °C	± 0.8 °C
°F	32 °F to 140 °F	0.1 °F	± 1.5 °F
* @ 23± 5°C			

Salt

Measurement Range	0 to 12 % salt (% weight).
Resolution	0.01 % salt.
Accuracy	0.5 % salt value * F.S. : full scale.

PATENT	CHINA : ZL 2008 2 0189918.5 ZL 2008 2 0189917.0 Germany : Nr. 20 2008 016 337.4	JAPAN : 3151214	TAIWAN : M 358970 M 359043 U.S.A. : Pending
--------	--	-----------------	--

* Appearance and specifications listed in this brochure are subject to change without notice.

1209-CD4317SD