

Data Sheet

IR608 Infrared Thermometer





No hassle warranty

TR4NSC4T



35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Point and press for quick and easy temperature measurement

The IR608 is an infrared thermometer with a laser pointer for easy targeting. A quick and effective diagnostic tool for identifying problems in a wide variety of applications

- "Pistol grip design" for comfortable grip
- Small enough to fit in your pocket
- Measuring range 18 °C to 400 °C
 (0 °F to 750 °F)
- Fixed emissivity at 0.95
- Laser sighting for accurate targeting (CE EN60825 certified Class II)

like HVAC/R, fire safety and protection, industrial maintenance automotive and quality control. The IR608 is robust yet lightweight with a solid ergonomic design.

- Display hold
- Fast response time
- Distance to spot size ratio 8:1
- Accuracy to 2 %
- Backlit display

Specifications (assumes ambient operating temperature of 23°C (73°F))

Function	Range	Accuracy
Temperature		
-	- 18 °C to 400 °C (0 °F to 750 °F)	
Temperature display	0.2 °C or 0.5 °F	
Targets	- 1 °C to 400 °C (30 °F to 750 °F)	± 2 % of reading or ± 2 °C
		(±3.5 °F), whichever is greater
	- 18 °C to - 1 °C (0 °F to 30 °F)	± 3 °C (± 5 °F) at 23 °C
		$(73 \text{ °F}) \pm 2 \text{ °C} (\pm 3.5 \text{ °F})$
Repeatability		± 2 % of reading or
		± 2 °C (± 3 °F)
Response time	500 mSec, 95 % response	
Emissivity	Pre-set 0.95	
Spectral response	7 to 18 μm	
Ambient operating	0 °C to 50 °C (32 °F to 120 °F)	
temperature		
Relative Humidity	10 % to 95 % RH non condensing, @ up to 30 °C (86 °F)	

General Specifications		
Storage temperature	– 20 °C to 65 °C (– 4 °F to 150 °F) without battery	
Weight / Dimensions	227 g (0.5 lb); 152 mm x 101 mm x 38 mm (6 in x 4 in x 1.5 in)	
Power	9 V Alkaline or NiCd battery	
Typical Battery life (Alkaline)	12 hours	
Distance to Spot Size	8:1	
Low Battery Indicator	Battery icon appears in display	
Warranty	One-year	

CE Certification

This instrument conforms to the following standards:

- EN 61326-1 Electromagnetic Emissions and Susceptibility
- EN 61010-1 General Safety
- EN 60825-1 Laser Safety

Meterman[®] The right tool, everyday.™

Meterman Test Tools





35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001