NETSCOUT.

Primary Device Attributes

Feature	LinkRunner G2	LinkRunner AT 2000	LinkRunner AT 1000
Android™-based[1] Smart Tester	●	x	x
Android-based App Support via NETSCOUT® App Store	●	x	x
On-board Chrome web browser	●	x	x
On-board Adobe .pdf reader	●	x	x
Speaker, mic, camera, flashlight, accelerometer, compass, gyro	●	x	x
USB	●	x	x
Micro USB	●	x	x
Micro SD	●	x	x
Large color display	●	x	x
Touch Screen	●	x	x
Extensible Platform	●	x	x
Wi-Fi Capable	●	x	x
Bluetooth/BLE Capable	●	x	x
10/100/1000BASE-T Copper	●	●	●
10/100BASE-X Fiber	●	●	x
Line rate packet reflector 1000BASE-T	●	●	x
IPv6 support	●	●	x

● = Included **x** = Not Included

Power

Feature	LinkRunner G2	LinkRunner AT 2000	LinkRunner AT 1000
Charge off PoE	●	x	x
Lithium ION rechargable battery	●	●	Option
AA battery pack	x	Option	●

Standard Test

Feature	LinkRunner G2	LinkRunner AT 2000	LinkRunner AT 1000
Negotiate PoE voltage (802.3at)	●	●	●
Negotiate PoE voltage (UPOE)	●	x	x
TruePower™ PoE load (25.5W)	●	●	x
TruePower™ PoE load up to UPOE (51W)	●	x	x
DHCP offer/response	●	●	●
1000BASE-T downshift warning	●	x	x
IP Address assignment	●	●	●
Proxy Configuration	●	●	●
Nearest switch (CDP/LLDP)	●	●	●
DNS server response support (2)	●	●	●
DNS server response support (4)	●	x	x
Gateway Router	●	●	●
Public facing IP address	●	x	x
Ping or TCP Port Open Reachability	●	●	●
Continuious Ping	●	●	●

Cable Test

Feature	LinkRunner G2	LinkRunner AT 2000	LinkRunner AT 1000
Distance to fault	●	●	●
Flash switch port	●	●	●
Integrated patch cable test	●	●	●
WireView support	●	●	●
Toning (analog and IntelliTone)	●	●	●

Configurable

Feature	LinkRunner G2	LinkRunner AT 2000	LinkRunner AT 1000
Proxy	●	●	●
DHCP or Static IP Support	●	●	●
Configurable PoE, Link, MAC and VLAN	●	●	●
Configurable 802.1X security	●	●	●

Reports

Feature	LinkRunner G2	LinkRunner AT 2000	LinkRunner AT 1000
Results saved locally on tester	Unlimited	50	10
LinkRunner™ AT Manager PC software	x	●	●
Link-Live Cloud Reporting	●	●	●

[1] Android is a trademark of Google Inc.