

PINTEK

HIGH VOLTAGE & HIGH FREQUENCY OSCILLOSCOPE PROBE



HVP-15HF



SPECIFICATION	
MAX.WORKING VOLTAGE	DC : 0~10KV DC AC : pulse ≤ 20 KV peak to peak AC : Sine wave ≤ 40 KV rms
SIGNAL / NOISE	≥ 60 dB(1KHz), ≥ 50 dB(1MHz)
BANDWIDTH	DC~40MHz(-3dB)
DIVISION RATIO	1 : 1000
RISE TIME	≤ 8.8 ns
INPUT RESISTANCE	100M Ω \pm 1 %
INPUT CAPACITANCE	3.0PF \pm 0.5PF
COMPENSATION RANGE	5PF~50PF
CABLE LENGTH	2.0METER(\pm 0.2M)
TEMPERATURE COFFICIENT	≤ 200 PPM / $^{\circ}$ C
DC ACCURACY	$\leq 3\%$ DC~10KV
SAFETY APP.	CE, GS, UL, CUL
OPERATING TEMPERATURE	0~50 $^{\circ}$ C
STORAGE TEMPERATURE	-20~+70 $^{\circ}$ C
WEIGHT / VOLUME	250g / ϕ 75*340mmL.



**IEC 1010
EN 61010**

SALES AGENT

※Specifications and appearance design subject to change without notice.